

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A disposable needleless injection device comprising a body supporting and/or delimiting a plurality of elements forming a circuit of elements, ~~this~~ the circuit comprising, from upstream to downstream, an initiation device associated with a pyrotechnic gas generator, a reservoir containing a liquid active principle that is to be injected and a system for injecting the active principle, the pyrotechnic gas generator comprising a pyrotechnic charge placed in a combustion chamber, said combustion chamber being divided into two volumes by a wall, ~~these~~ the two volumes being defined, from upstream to downstream, as a first volume in which the pyrotechnic charge is placed and a second volume, the two volumes communicating via a first device for regulating ~~the~~ a pressure level in the combustion chamber, said injection device ~~being characterized in that it comprises~~ further comprising an expanding membrane, initially furled, constituting a sealed wall between the combustion chamber and the reservoir of active principle, said membrane being able, in operation, to deploy under the action of the gases originating from the combustion of the pyrotechnic charge.

2. (Currently Amended) The device as claimed in claim 1, ~~characterized in that~~ wherein the first device for regulating the pressure level ~~consists of~~ includes a passage formed through the wall.

3. (Currently Amended) The device as claimed in claim 1, ~~characterized in that~~ wherein the pyrotechnic charge is arranged in a first sub-volume of the first volume of the combustion chamber, this first sub-volume being initially closed.

4. (Currently Amended) The device as claimed in claim 3, ~~characterized in that~~ wherein the first sub-volume of the first volume of the combustion chamber is separated, by a

second device for regulating the pressure level, from a second sub-volume of the first volume of the combustion chamber which is situated downstream of the first sub-volume.

5. (Currently Amended) The device as claimed in claim 4, ~~characterized in that~~ wherein the second regulating device ~~consists of~~ includes a calibrated rupture disk.

6. (Currently Amended) The device as claimed in claim 5, ~~characterized in that~~ wherein the first sub-volume of the first volume, in which the pyrotechnic charge is placed, is delimited in part by the walls of a cartridge inserted in the body of the device.

7. (Currently Amended) The device as claimed in claim 6, ~~characterized in that~~ wherein the pyrotechnic charge is placed in the cartridge between the calibrated rupture disk and a detonator able to initiate the pyrotechnic charge.

8. (Currently Amended) The device as claimed in claim 7, ~~characterized in that~~ wherein the cartridge has the shape of an L-shaped duct in which the pyrotechnic charge is placed, ~~this~~ the duct being blocked off at one of its ends by the detonator and at its other end by the calibrator rupture disk.

9. (Currently Amended) The device as claimed in claim 2, ~~characterized in that~~ wherein the membrane deploys into the reservoir of active principle.

10. (Currently Amended) The device as claimed in claim 9, ~~characterized in that~~ wherein the passage is offset from a longitudinal central axis of the combustion chamber and is formed in such a way as to be as far as possible away from the membrane.